



#52 SPRAY ADHESIVE®



RCD Corporation #52 Spray Adhesive® is formulated to bond insulation to galvanized and aluminum sheet metals. This adhesive has low soak-in properties and bonds to a variety of construction surfaces - from paper to metal. This handy and compact aerosol can is portable, eliminates expensive application equipment, the time consuming clean-up process and saves valuable floor space too. Wide web spray pattern allows greater coverage in less time.

- **Fast Tacking**
- **Wide Webbing Spray Pattern**
- **Flammable**
- **VOC compliant**

Application

#52 Spray Adhesive® works best at 75° F. Shake can for at least one minute prior to spraying. Surfaces must be free from algae, corrosion, dirt, grease, mold, mildew, oil, scale, silicone & water. Hold can upright, point valve toward surface & spray from a distance of 6 to 8 inches, apply a light film while moving can to avoid build up on the substrate. It is recommended to test the performance and compatibility with the intended substrates prior to use.

Temporary Bond: Spray lightly on one surface.

Permanent Bond: Spray both surfaces to be bonded. Allow time to tack, then bond.

Cleaning Spray Tip: When finished, turn the can upside down & spray for two seconds to clear actuator valve. If adhesive accumulates at the tip, wipe clear while wet. Degreasing solvent can be used to unclog spray tip.

Catalog Number: 300520
Net Weight: 12 oz. (340g)
Shelf Life: 12 months (unopened container)
Service Temperature Limits: . . . -20° F to 185°F.
Storage Temperature: 45°F to 85°F.

Precautions

It is the applicator's responsibility for the design, use and storage of all building materials, including RCD Corporation® #52 Spray Adhesive®. Store at temperatures of 45° to 85° F. Rotate inventory using first in first out method (FIFO). Protect from freezing. Occupants and users who are chemically sensitive, prone to allergic reactions or have respiratory ailments of any kind should consult their physician before coming into contact with aerosol products.

DANGER

Contents under pressure and flammable. Vapors may ignite easily. Keep away from heat, sparks, and open flames. Turn off pilot lights, heaters, electric motors, and other sources of ignition. Do not spray onto energized circuits. Do not puncture or incinerate (burn) container, even when empty. Do not expose to heat above 120°F. Do not place can on hot surfaces or in direct sunlight. Heat may cause can to burst violently. **KEEP OUT OF REACH OF CHILDREN.**

Cautions

Do not ingest this product. Avoid eye contact. Avoid prolonged skin contact. Avoid breathing vapors and aerosols. Use in well ventilated area. Do not smoke while using. Intentional inhalation abuse (concentrating and inhaling vapors) is harmful and may be fatal. Appropriate respiratory protection is required when using this product.

First Aid

Skin Contact: Wash affected areas with soap and water. Seek medical attention if irritation develops and persists.

Eye Contact: Flush eyes either clear water for at least 15 minutes. Seek medical attention if irritation develops and persists.

Ingestion: Do Not Induce Vomiting. Seek medical attention immediately.

Inhalation: Provide fresh air. Respire if needed. Seek medical attention immediately.

Warranty

Since methods of application, storage, and on-site conditions are beyond RCD Corporation's control and can affect performance, RCD makes no warranties. All other warranties, express or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose, are disclaimed. It is understood and agreed that seller's liability, whether in contract, tort, warranty, negligence, personal injury, wrongful death or otherwise shall not exceed the return of the amount of the purchase price paid by the purchaser and under no circumstances shall seller be liable for special, indirect or consequential damages. The price paid for the product is consideration in limiting seller's liability.