



Safety Data Sheet

Issue Date: 01-Jun-2012

Revision Date: 09-Jan-2025

Version 1

1. IDENTIFICATION

Product Identifier

Product Name #15 Weather Barrier Coating®

Other means of identification

SDS # RCD 15

Recommended use of the chemical and restrictions on use

Recommended Use Coat insulation, air ducts, roofs, interior or exterior walls.

Details of the supplier of the safety data sheet

Supplier Address

RCD Corporation
2850 Dillard Road
Eustis, FL 32726
www.rcdmastics.com

Emergency Telephone Number

Company Phone Number 352-589-0099
Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance White viscous liquid

Physical state Viscous liquid

Odor Pleasant

Classification

This chemical does not meet the hazardous criteria set forth by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). However, this Safety Data Sheet (SDS) contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

3. COMPOSITION/INFORMATION ON INGREDIENTS

The product contains no substances which, at their given concentration, are considered to be hazardous to health. However, additional component information is available in subsequent sections of this SDS.

| Chemical Name | CAS No. | Weight-% |
|----------------------|------------|----------|
| Ground Limestone * | 1317-65-3 | 20-30 |
| Titanium(IV) Oxide * | 13463-67-7 | 5-10 |
| Zinc Oxide * | 1314-13-2 | 1-5 |
| Aluminum Hydroxide * | 21645-51-2 | 1-5 |

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

*As respirable dust, nuisance dust only. Normal application procedures pose no hazard since these ingredients are encapsulated, but grinding or sanding dried films may yield respirable dusts.

4. FIRST AID MEASURES

First Aid Measures

| | |
|---------------------|--|
| Eye Contact | Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Inorganic particulate materials may cause mechanical irritation. Seek immediate medical attention/advice. |
| Skin Contact | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. DO NOT USE SOLVENTS OR THINNERS to remove from skin. Get medical attention if irritation occurs. |
| Inhalation | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician. If breathing is difficult, oxygen should be administered by qualified personnel. |
| Ingestion | Do NOT induce vomiting. Drink plenty of water or milk immediately. Call a poison center or doctor/physician if you feel unwell. |

Most important symptoms and effects

| | |
|-----------------|--------------------------------|
| Symptoms | May cause mild eye irritation. |
|-----------------|--------------------------------|

Indication of any immediate medical attention and special treatment needed

| | |
|---------------------------|------------------------|
| Notes to Physician | Treat symptomatically. |
|---------------------------|------------------------|

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical or CO2. Water fog. Universal foam.

Unsuitable Extinguishing Media Not applicable.

Specific Hazards Arising from the Chemical

Product is not flammable or combustible. Thermal decomposition can lead to release of irritating and toxic gases and vapors.

Hazardous Combustion Products Carbon monoxide. Carbon dioxide (CO2).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

| | |
|-----------------------------|---|
| Personal Precautions | Use personal protection recommended in Section 8. |
|-----------------------------|---|

Environmental precautions

| | |
|----------------------------------|---|
| Environmental precautions | Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. |
|----------------------------------|---|

Methods and material for containment and cleaning up

| | |
|--------------------------------|--|
| Methods for Containment | Provide ventilation. Prevent further leakage or spillage if safe to do so. Soak up and contain spill with an inert (i.e. vermiculite, dry sand or earth) absorbent material. |
| Methods for Clean-Up | Sweep up and shovel into suitable containers for disposal. Clean up in accordance with all applicable regulations. For waste disposal, see section 13 of the SDS. |

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling

Avoid breathing dust/fume/gas/mist/vapors/spray. Use personal protection recommended in Section 8. Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Store away from incompatible materials. Store away from heat, sparks, flame. Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible Materials

Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|----------------------------------|--|---|--|
| Ground Limestone 1317-65-3 | - | TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction | TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust |
| Titanium(IV) Oxide 13463-67-7 | TWA: 10 mg/m ³ | TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust | IDLH: 5000 mg/m ³ |
| Aluminum Hydroxide 21645-51-2 | TWA: 1 mg/m ³ respirable fraction | - | - |
| Zinc Oxide 1314-13-2 | STEL: 10 mg/m ³ respirable fraction TWA: 2 mg/m ³ respirable fraction | TWA: 5 mg/m ³ fume TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ fume (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) STEL: 10 mg/m ³ fume | IDLH: 500 mg/m ³ Ceiling: 15 mg/m ³ dust TWA: 5 mg/m ³ dust and fume STEL: 10 mg/m ³ fume |

Appropriate engineering controls

Engineering Controls

Apply technical measures to comply with the occupational exposure limits. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area. Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Chemical safety goggles/faceshield. Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection

Chemical resistant, impermeable gloves. Suitable protective clothing. Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection

Wear an appropriate NIOSH/MSHA approved respirator. Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | | | |
|-----------------------|----------------------|-----------------------|----------------|
| Physical state | Viscous liquid | Odor | Pleasant |
| Appearance | White viscous liquid | Odor Threshold | Not determined |
| Color | White | | |

| <u>Property</u> | <u>Values</u> | <u>Remarks • Method</u> |
|-------------------------------------|-----------------------|--------------------------------|
| pH | 7.0-8.0 | |
| Melting Point/Freezing Point | 0 °C / 32 °F | |
| Boiling Point/Boiling Range | 100 °C / 212 °F | |
| Flash Point | > 162.7 °C / > 325 °F | Tag Open Cup |
| Evaporation Rate | Same as water | |
| Flammability (Solid, Gas) | Non-flammable | |
| Flammability Limits in Air | | Not applicable |
| Upper Flammability Limits | Not applicable | |
| Lower Flammability Limit | Not applicable | |
| Vapor Pressure | Equal to water | |
| Vapor Density | equal to water | |
| Relative Density | >1.30 | |
| Water Solubility | Miscible in water | |
| Solubility in other solvents | Soluble | |
| Partition Coefficient | Not determined | |
| Auto-ignition Temperature | Not applicable | |
| Decomposition Temperature | >1000° F / >537.7° C | |
| Kinematic Viscosity | 1,017 cSt | |
| Dynamic Viscosity | 12,000 cps | |
| Explosive Properties | None - Stable | |
| Oxidizing Properties | None - Stable | |

Other Information

VOC Content <50 g/L

10. STABILITY AND REACTIVITY**Reactivity**

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to Avoid

Heat, flames and sparks.

Incompatible Materials

Strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Product Information****Eye Contact**

May cause irritation to the eyes.

| | |
|---------------------|---|
| Skin Contact | Not a primary skin irritant. |
| Inhalation | Not an expected route of exposure. |
| Ingestion | The systemic toxicity of this substance has not been determined. However, it should be practically non-toxic to internal organs if swallowed. |

Component Information

| Chemical Name | ATEmix (oral) | ATEmix (dermal) | Inhalation LC50 |
|----------------------------------|-----------------------|-----------------|-----------------|
| Titanium(IV) Oxide 13463-67-7 | > 10000 mg/kg (Rat) | - | - |
| Aluminum Hydroxide 21645-51-2 | > 5000 mg/kg (Rat) | - | - |
| Zinc Oxide 1314-13-2 | > 5000 mg/kg (Rat) | - | - |

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity Titanium dioxide is a possible carcinogen when it appears as a respirable dust. Normal application procedures pose no hazard since these ingredients are encapsulated, but grinding or sanding dried films may yield respirable dusts.

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|----------------------------------|-------|----------|------------------------|------|
| Titanium(IV) Oxide 13463-67-7 | | Group 2B | | X |
| Zinc Oxide 1314-13-2 | | | Reasonably Anticipated | X |

Legend

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 22,465.00 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

The ecological toxicity of this product is not known.

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Not determined

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

This product contains one or more substances that are listed with the State of California as a hazardous waste

| Chemical Name | California Hazardous Waste Status |
|-------------------------|-----------------------------------|
| Zinc Oxide 1314-13-2 | Toxic |

14. TRANSPORT INFORMATION

Note

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

Not regulated

IATA

Not regulated

IMDG

Not regulated

15. REGULATORY INFORMATION

International Inventories

| Chemical Name | TSCA | DSL/NDSL | EINECS/E LINCS | ENCS | IECSC | KECL | PICCS | AICS |
|------------------------|------|----------|-------------------|---------|-------|---------|-------|------|
| Ground Limestone | X | X | X | Present | X | Present | X | X |
| Titanium(IV) Oxide | X | X | X | Present | X | Present | X | X |
| Aluminum Hydroxide | X | X | X | Present | X | Present | X | X |
| Zinc Oxide | X | X | X | Present | X | Present | X | X |
| 1,2 Propanediol | X | X | X | Present | X | Present | X | X |
| Hydroxyethyl Cellulose | X | X | | Present | X | Present | X | X |

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name | CAS No. | Weight-% | SARA 313 - Threshold Values % |
|------------------------|-----------|----------|-------------------------------|
| Zinc Oxide - 1314-13-2 | 1314-13-2 | 1-5 | 1.0 |

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical Name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|---------------|-----------------------------|------------------------|---------------------------|----------------------------|
| Zinc Oxide | | X | | |

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

| Chemical Name | California Proposition 65 |
|---------------------------------|---------------------------|
| Titanium(IV) Oxide - 13463-67-7 | Carcinogen |

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|----------------------------------|------------|---------------|--------------|
| Ground Limestone 1317-65-3 | X | X | X |
| Titanium(IV) Oxide 13463-67-7 | X | X | X |
| Zinc Oxide 1314-13-2 | X | X | X |
| 1,2 Propanediol 57-55-6 | X | | X |

16. OTHER INFORMATION

| NFPA | Health Hazards | Flammability | Instability | Special Hazards |
|-------------|-----------------------|---------------------|-------------------------|----------------------------|
| | 1 | 0 | 0 | - |
| HMIS | Health Hazards | Flammability | Physical hazards | Personal Protection |
| | 1 | 0 | 0 | B |

Issue Date: 01-Jun-2012
Revision Date: 09-Jan-2025
Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet